



PIN	SIGNAL
1	/CS1
2	/RST
3	A0
4	SCK
5	CDA
6	VDD
7	VSS
8	VDOUT
9	C3+
10	C1-
11	C1+
12	C2+
13	C2-
14	C4+
15	V4
16	V3
17	V2
18	V1
19	V0
20	VR
21	IRS

NOTE:

1. GENERAL TOLERANCE: ±0.20.
2. (...) IS REFERENCE DIMENSION.
3. COMPLY ROHS.
4. * CRITICAL DIMENSION.



DETAIL: DOTS (10:1)

Display Type	STN(GRAY)
	POSITIVE
	REFLECTIVE
Front Polarizer	
Operating Method	1/65 DUTY,1/9 BIAS
Viewing Angle	6 °CLOCK
LCD Driver IC	1ST3004
Driver Voltage	VDD=5.0V
Operating Voltage	VLCD=9.8V
Operation Temperature	-20°C TO 70°C
Storage Temperature	-30°C TO 80°C
Interface	Serial/6800/8080

					DRAWN	LJW	TITLE	DRAWING NO.			
					EE.CHECKED	TJP	MODULE SPEC.	STR-TG9190			
					ME.CHECKED	TJP	BOM No: BM130820-04A	UNIT	mm	SCALE	FIT
					APPROVED	HJB		3rd Angle		SHEET	1 OF 1
01		First Issue		LJW	13.08.22	CUSTOMER'S APPROVAL	TRUEVISION TECHNOLOGIES LTD				
VER.	SYMBOL	AMENDMENT		SIGN	DATE						