



FPC DEFINE

| PIN | SYMBOL |
|-----|---------|
| 1 | LED-K |
| 2 | LED-A |
| 3 | ESD-GND |
| 4 | CS0 |
| 5 | RST |
| 6 | CD |
| 7 | SCK |
| 8 | SDA |
| 9 | VDD |
| 10 | VSS |
| 11 | VBO+ |
| 12 | VBO- |
| 13 | VB1- |
| 14 | VB1+ |
| 15 | VLCD |
| 16 | ESD-GND |

NOTE:

1. GENERAL TOLERANCE: ± 0.3 .
2. (...) IS REFERENCE DIMENSION.
3. * CRITICAL DIMENSION
4. COMPLYABLY RoHS.
5. ACF for COG of IC: CP6920F3(3um Filler).
6. ITO Glass:With Hard Coat at both sides.



| | |
|-----------------------|--------------------------------|
| DISPLAY TYPE | FSTN |
| | POSITIVE |
| | TRANSFLECTIVE |
| OPERATION VOLTAGE | 9.0V |
| vdd | 3.3V |
| OPERATING METHOD | 1/5 BIAS |
| | 1/33 DUTY |
| VIEWING ANGLE | 6:00 |
| OPERATION TEMPERATURE | -10° C TO 60° C |
| STORAGE TEMPERATURE | -20° C TO 70° C |
| CONNECTOR TYPE | FPC |
| LCD CONTROLLER/DRIVER | UC1701x |
| BACKLIGHT COLOR | WHITE, Vt=3.1V, If=30mA (typ.) |

| VER. | SYMBOL | AMENDMENT | SIGN | DATE | CUSTOMER'S APPROVAL | DRAWN | ZC | TITLE | DRAWING NO. |
|------|--------|-------------|------|----------|---------------------|------------|-----|----------------------|------------------------------|
| 01 | | First issue | ZC | 14.11.05 | | EE.CHECKED | TJP | MODULE SPEC. | STR-TG9372 |
| | | | | | | PE.CHECKED | TJP | | |
| | | | | | | APPROVED | HJB | | |
| | | | | | | | | BOM NO.:BM140807-08A | UNIT mm SCALE FIT |
| | | | | | | | | | 3rd Angle SHEET 1 OF 1 |
| | | | | | | | | | TRUEVISION TECHNOLOGIES LTD. |